

SKD-1103

1 or 2 Lines
SIP Phone

SKD-1203



- 1 or 2 lines SIP phone.
- Message waiting indicator.
- 3 customizable service dials (Up to 10).
- Faceplate with customizable hotel logo.

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.



1. Features

	Keys	1203	1103
		- Dial keys (0~9, *, #) - Line keys Line1, Line2 with red color LED - Function keys Hold, Redial, Volume up/down, 3 Service dial keys	(0~9, *, #) - N/A - Hold, Redial, Volume up/down, 3 Service dial keys
Phone Features		- One or Two Lines 3 programmable service dial keys(Up to 10) - Red color message waiting indicator for ringing and message waiting	- Handset and ringer volume control - Redial last call - Call Hold and resume
Easy Administration		- Web GUI. - Auto provisioning	Firmware upgrade via web.
Codec		G.711 (a-law, μ-law)	
Network Protocol		- HTTP server - ToS / VLAN IEEE 802.1 p/q	Static IP, DHCP Client
SIP		SIP V2 (RFC3261)	
Security		- Web login authentication for web setup - TLS 1.2	MD5 for SIP authentication (RFC2069/ RFC2617)
DTMF		In-Band / Out-of-Band DTMF(RFC2833) / SIP Info (RFC2976)	
Voice Quality		- CNG: Comfortable noise generator - Echo canceller: LEC / AEC - Jitter buffer/PLC	
Tones		Ring back tone (local), Busy tone, Dial tone	

2. Hardware Specifications

LED Indications	Line keys and Message waiting indicator
Power	- PoE : IEEE 802.3af compliant - AC adaptor: Input: 100 ~ 240 VAC, Output: 5.9V / 1A (optional)
Jacks	RJ45 10/100 Mbs: LAN port x 1,DC jack x 1, RJ9 Handset jack x 1
Ethernet cable	9 feet x 1
Size and Weight	Dimensions: 224 (L) x108mm(W) x 124mm(H), Weight: 770g

3. Regulatory

	USA	EU
EMI	FCC Part 15B	EN55032
Safety		EN60950-1
EMC		EN55024
		EN61000-3-2
		EN61000-3-3
		IEC61000-4-2
		IEC61000-4-3
RoHS	Comply with directive 2002/95/EC RoHS (as amended by commission decision 2005/613/EC)	EC61000-4-4
Temperature	- Storage: Low temperature at -10°C - Operating Low temperature at +5°C	- High temperature at +60°C - High temperature at +35°C

Model:

SKD-1103-01

SKD-1203-01

SKD-1103-01TI

SKD-1203-01TI

