AEi COMMUNICATIONS

Serving the Hospitality Industry with Advanced **IP and Analog** Telephony Solutions **Worldwide**

SFT-1100 Series

Single Line Wall-Mount Corded SIP Telephone

SFT-1100

Features

- Single Line Telephone
- Full Duplex Handset
- Magnetic Hookswitch
- Wall Mountable Only
- Hearing Aid Compatible
- Volume Control, Hold and Mute
- Message Waiting & Ring Indicator on Handset
- Customizable Hotel Logo and Dialing Instructions on Faceplate

AEi brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEi** your satisfaction is our priority.

www.aeicommunications.com

AEI COMMUNICATIONS

Serving the Hospitality Industry with **Advanced IP and Analog** Telephony Solutions **Worldwide**

PRODUCT

SFT-1100-NK Lobby
Single Line Wall-Mount
Corded Telephone
No Guest Service Keys
No DTMF Keys

SFT-1103
Single Line Wall-Mount
Corded Telephone
Three Guest Service Keys

SPECIFICATIONS

Power	• Adapter 100-240 VAC Output 6V/1A (Optional)
	• PoE IEEE802.3af
Jacks	• 10/100 RJ45 WAN • RJ9 Handset
Dimensions	• 200mm(L)x85mm(W)x35mm(H) (7.87"x3.35"x1.38")
Weight	• 400g
Easy	• GUI
Administration	• Web Based speed-dial key setting for m1-m6
	• Firmware Upgrade via Web
	• Auto Provisioning
	• IP Address auto announcement from Handset
Codec	• G.711a Option G.729
Network Protocol	• Telnet / http Server / DNS Client
	• PPPoE / Static / DHCP Client IP assignment.
	• ToS field / VLAN IEEE 802.1 p/q
SIP	• SIP V1 (RFC2543) SIP V2 (RFC3261)
Security	• Web Login authentication for web setup
	• MD5 for SIP authentication (RFC2069/ RFC2617)
Voice Quality	• CNG Comfortable Noise Generator
	• LEC Line Echo Canceller • Jitter Buffer
	• VAD Voice Activity Detection • Packet Loss Compression
EMI	USA: FCC Part 15B,D ICES-003 EU: EN 55022
EMC	EU: EN 55024, EN 61000-4-4, EN 61000-3-2, IEC 61000-4-5
	EN 61000-3-3, IEC 61000-4-6, EN 61000-4-2, IEC 61000-4-11
RoHS	• Comply with directive 2002/95/EC RoHS (2005/613/EC)
Temperature	• Storage -10C to +60C • Operating 0C to +40C

FC CE RoHS

1001 Broadway 2D Millbrae, CA 94030 USA Tel: 650.552.9416