

SSP-9210-SM

Two-Line Coded
VoIP Speakerphone
DECT Base Station



Features

- Auto Line Select
- 3-way Conference
- Line in use Indicator
- 2-line Speakerphone
- Hearing Aid Compatible
- Unique Customizable Faceplate
- Message Waiting & Ring Indicator
- Integrated Cordless Base Station
- Link Up to 3 DECT Cordless Handsets
- 10 Programmable Guest Service keys
- Adjustable Handset & Speakerphone Volume Control

AEI brings cutting-edge telephony solutions to the most prestigious hotels and resorts worldwide. Our feature rich telephones exceed the expectations of the most demanding hoteliers with high quality, impeccable workmanship and stylish products.

At **AEI** your satisfaction is our priority.



PRODUCT OPTIONS



SSP-9210-SM
Two-Line Telephone
10 Guest Service Keys
with Speakerphone

SPECIFICATIONS

Power	<ul style="list-style-type: none"> • Adapter 100-240 VAC Output 6V/1A (Optional) • PoE module Class 0
Jacks	<ul style="list-style-type: none"> • 10/100 RJ45 WAN • RJ9 Handset • DC Jack
Color	<ul style="list-style-type: none"> • Black, Textured
Dimensions	<ul style="list-style-type: none"> • 230mm(L)x160mm(W)x45mm(H) (9.06"x6.30"x1.75")
Weight	<ul style="list-style-type: none"> • 880g
Cords	<ul style="list-style-type: none"> • 10' Line Cord (15' Upon Request) & 10' Coiled Cord
Handset	<ul style="list-style-type: none"> • Hearing Aid Compatible
DECT Master	<ul style="list-style-type: none"> • DECT / GAP Compatible
RF Band	<ul style="list-style-type: none"> • EU Band 1881.792 (ch0) - 1897.344 (ch9) (10 Channels) • US Band 1921.536 (ch0) - 1928.448 (ch4) (5 Channels)
Cannel Space	<ul style="list-style-type: none"> • 1728 Khz • Bit Rate 1150 Kbit/s
Tx Power	<ul style="list-style-type: none"> • 100mW • GFSK
RF Range	<ul style="list-style-type: none"> • Outdoor 984 Feet • Indoor 164 Feet (DOM)
Easy Administration	<ul style="list-style-type: none"> • GUI • Firmware Upgrade via TFTP/HTTP, Auto Provisioning
Codec	<ul style="list-style-type: none"> • G.711/G.729
Network Protocol	<ul style="list-style-type: none"> • HTTP/DHCP Server • Static / DHCP IP assignment. • ToS field / VLAN IEEE 802.1 p/q
SIP	<ul style="list-style-type: none"> • SIP V2 (RFC3261)
Security	<ul style="list-style-type: none"> • Web Login authentication for web setup • MD5 for SIP authentication (RFC2069/ RFC2617)
DTMF	<ul style="list-style-type: none"> • In Band / Out of Band DTMF (RFC2833) / SIP Info (RFC2976)
Voice Quality	<ul style="list-style-type: none"> • CNG Comfortable Noise Generator • LEC/AEC Line Echo Canceller • Jitter Buffer/PLC
EMI	USA: FCC Part 15B,D
EMC	EN 55022, EN 600950-1, EN 55024
RoHS	EN 61000-3-2,3-3, IEC 61000-4-2,4-3, IEC 61000-4-4,4-5,4-6,4-11
	• Comply with directive 2002/95/EC RoHS (2005/613/EC)