

Product Introduction

This curtain track series features a flexible telescopic design, which can precisely adapt to different household window widths. It can easily cover everything from narrow windows to wide view windows without additional customization, allowing for more flexible installation and layout. With precision transmission and a stable structure, the curtains open and close smoothly. Combined with a universal installation solution and a complete set of standard accessories, it makes installation and use highly efficient and convenient, bringing a hassle-free and smooth curtain control experience for daily home use.

Features

- Multi-size telescopic design, suitable for all window widths
- Universal for top and side mounting, flexible installation
- Dual transmission and dual brackets, stable drive and firm structure
- Reversing transition assembly, smooth opening and closing without jamming
- Complete accessories, one-stop assembly



Specification

- Model Number: CT183 / CT234 / CT2545
- Adjustable extension range: 1.8–3m / 2.3–4m / 2.5–4.5m
- External dimensions:
 - Width (including mounting brackets): 67mm
 - Height (including mounting brackets): 54mm
 - Length (minimum state): 1720mm / 2220mm / 2470mm
- Rail wall thickness: 1mm
- Linear speed: 90mm per revolution
- Rated load: 20kg (10kg for single side)
- Applicable curtain type: double open-close curtain
- Belt specification: module 1.59, pitch $Pd=5$, width $B=10$ mm, length $L=2160$ mm
- Flat strap specification: thickness 1mm, width 10mm, length 6180mm

Product Dimension Diagram (mm)

