

Push Button Emergency Station

The palm-size Akuvox E20S Push Button Emergency Station is ruggedized with 316-grade stainless steel. E20S can be used on 1299 and single in-wall box.



At a Glance

- ☒ Vandal resistant body, with a panic button;
- ☒ Linux operation system;
- ☒ Two-way audio communication over IP networks with Echo Cancellation feature;
- ☒ Flush-mounted;
- ☒ Complies with SIP standard;
- ☒ For indoor use only;

Physical & Power

- | | |
|--|---|
| <ul style="list-style-type: none"> ☒ Front panel: 316 grade stainless steel ☒ Button: 1 call button ☒ Ethernet port: RJ45, 10/100Mbps adaptive ☒ Microphone: 1 ☒ Speaker: 1 ☒ 802.3af Power-over-Ethernet ☒ Size: 100x100x38 mm ☒ Installation: Flush-mounted ☒ IK Rating: IK10 ☒ Working Humidity: 10~90% ☒ Working Temperature: -20° C ~ +55° C ☒ Storage Temperature: -25° C ~ +60° C | <ul style="list-style-type: none"> ☒ SIP Protocol: SIP v1 (RFC2543), SIP v2 (RF3261) ☒ SIP account: 1 SIP account ☒ Audio codecs: G.711a, G.711 μ, G.722 ☒ QoS support: Yes ☒ Auto Answer support: Yes ☒ Network mode: DHCP or Static IP ☒ System time: NTP for auto time setting ☒ Protocols support: IPv4, HTTP, HTTPS, FTP, DNS, NTP, RTP, TCP, UDP, ICMP, DHCP, ARP |
|--|---|