## Akuvox R25A

#### Perfect Doorphone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone R25A enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure.

#### At a Glance

- Single speed-dial button with blue backlight;
- Linux operation system;
- Wide-angle camera: 150° (H), 150° (V);
- Two-way audio communication over IP networks with Echo Cancellation & Noise suppression;
- Flush-mounted & surface-mounted;
- Complies with SIP & ONVIF;

#### Physical & Power

- Front panel: Aluminum
- Camera: 4M pixels, automatic lighting
- Button: 1 call button
- Light sensor: Support
- Motion sensor: Support
- Wiegand port: Support
- RS485 port: Support
- RF card reader: 13.56MHz & 125kHz, NFC
- Relays out: 2
- Inputs: 2
- Microphone: 1

- Speaker: 1
- Tamper alarm: Support
- Ethernet port: RJ45, 10/100Mbps adaptive
- 802.3af Power-over-Ethernet
- IP Rating: IP65
- Size: 145x85x24.8mm
- Installation: Flush-mounted or Wall-mounted
- Working Humidity: 10~90%
- Working Temperature: -40°C ~ +55°C
- Storage Temperature: -40°C ~ +70°C



# Datasheet



Akuvox R25A

## Datasheet

#### Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- $\bullet$  Narrowband audio codec: G.711a, G.711 $\mu$
- Wideband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

#### Video

- Sensor: 1/3.2", CMOS
- Pixels: CIF, VGA, 4CIF, 720p, 1080p, 2K
- Video codec: H.264
- Video resolution: up to 2000x2000
- Max. image transfer rate: 2K 30fps
- Viewing angle: 150°(H) / 150°(V)
- High intensity IR LEDs for picture lighting during dark hours with internal light sensor
- Compatible to 3<sup>rd</sup>party video components,
  e.g. NVRs

### Door Entry Feature

- Relays controlled individually by DTMF tones
- Camera permanently operational
- Auto-night mode with LED illumination
- White balance: auto
- Minimum illumination: 0.1LUX

#### Networking & Protocol

 Protocols support: IPv4, HTTP, HTTPS, FTP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

#### Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Entry log export
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)

## **Application Scenario**

- Office door phone with on-site or hosted IP-PBX
- Remote site entry over Internet
- Apartment/flat intercom with door access control



Akuvox\_202309\_V6.0