

Perfect Doorphone choice for daily life

The security that comes with being able to control who comes into your building along with the ability to verbally and visually confirm their identity is immeasurable. Akuvox's Video Doorphone R29C enables you to easily monitor an entrance door or gate and gives you the peace of mind knowing that your facility is more secure.

At a Glance

- Aluminum panel with 7inch touchscreen;
- Android operation system;
- Wide-angle camera: 105° (H), 55° (V);
- Two-way audio communication over IP networks with Echo Cancel feature;
- Multi-way access feature including: Face, EM/Mifare Card, PIN, BLE & QR code;
- Flush-mounted & surface-mounted;
- Complies with SIP & ONVIF;



Physical & Power

- | | |
|--|--|
| • Front panel: Aluminum | • Microphone: 1 |
| • Display: 7 Inch IPS LCD | • Speaker: 1 |
| • Screen: 7 Inch capacitive touch screen | • BLE: Support BT5.0 |
| • Main Camera: 2M pixels, automatic lighting | • Tamper Alarm: Support |
| • Auxiliary Camera: 1M pixels | • Ethernet port: RJ45, 10/100Mbps adaptive |
| • Light sensor: Support | • 802.3at Power-over-Ethernet |
| • Motion sensor: Support | • 12V DC connector (if not using PoE) |
| • Wiegand port: 1ch input/output(selectable) | • IP Rating: IP65 |
| • RS485 port: Support | • IK Rating: IK06 |
| • RF reader: 13.56MHz&125kHz, NFC (only Android) | • Installation: Flush-mounted & Wall-mounted |
| • Relays out: 3 | • Dimension (HxWxD): 324x130x27mm |
| • Inputs: 3 | • Working Humidity: 10~90% |
| | • Working Temperature: -20°C ~ +55°C |
| | • Storage Temperature: -40°C ~ +70°C |

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711μ
- Wideband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator

Video

- Sensor: 1/2.8", CMOS
- Pixels: CIF, QCIF, VGA, 4CIF, 720p, 1080p
- Video codec: H.264
- Video resolution: up to 1920x1080
- Max. image transfer rate: 1080p – 25fps
- Viewing angle: 105°(H) / 55°(V)
- High intensity IR LEDs for picture lighting during dark hours with internal light sensor
- White LEDs for QR code scanning
- Compatible to 3rd-Party-Video components,

Networking and Protocol

- Protocols support: IPv4, HTTP, HTTPS, FTP, DNS, NTP, RTSP, RTP, TCP, UDP, ICMP, DHCP, ARP

Door Entry Feature

- Relays controlled individually by DTMF tones
- Multi-way Unlock: Face, EM/Mifare Card, PIN, QR and BLE
- Camera permanently operational
- White balance: auto
- Minimum illumination: 0.1LUX

Capacity

- User: 20,000
- Face Templates: 20,000
- Card: 100,000
- PIN: 20,000

Card Type

- EM card
- Mifare card
- DesFire card (EV1/EV2/EV3)
- Felica card

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Entry log export
- Access table export / import
- Firmware upgrade
- System logs (include door access logs)