Akuvox S563W Datasheet

Premium Indoor Monitor for Your Home

The Akuvox S563W is an 8-inch SIP indoor monitor that runs on the Android 12 operating system. It features an exceptional speaker and a high-resolution touchscreen display, ensuring an unparalleled audio-visual intercom experience. Its stylish and space-saving design blends seamlessly into modern homes.

3:40 AM | 21° 2070 03:31 - Wed | 2

At a Glance

- Seamless compatibility with Android 12 OS
- Exceptional two-way audio communication
- Completely solve the stability problem of Wi-Fi with Wi-Fi 6;
- Easy integration with SIP PBXes
- Powered by PoE or an external power supply
- Voice changer function to protect vulnerable individuals
- Compatible with US or European electrical wall boxes
- Built-in smart voice assistant

Physical & Power

- Front panel: Plastic
- RAM / ROM: 2GB / 8GB
- Display: 8 Inch IPS LCD
- Screen: 8 Inch capacitive touch screen
- Wi-Fi: IEEE802.11 b/g/n/ax
- Bluetooth:4.2
- RS485 Port: Support
- Relays Out: 1
- Bell in: 1
- Alarm Input: 8

- Microphone: one microphone, -26dB
- Speaker: one speaker, 4Ω / 2W
- Ethernet Ports: 2xRJ45, 10/100Mbps adaptive
- 802.3af Power-over-Ethernet
- 12V DC Connector (if not using PoE)
- Tamper Resistant: Support
- Installation: Wall-mounted & Desktop
- Dimension: 216.2x124.4x22.1 mm
- Working Humidity: 10~90%
- Working Temperature: -10°C ~ +45°C
- Storage Temperature: -20°C ~ +70°C

Akuvox S563W Datasheet

Touch Screen Display

• Display Mode: Normally black, Transmissive

• LCD Size: 8 inch (Diagonal)

• Aspect Ratio: 16:10

• Resolution: 1280x800

• Contrast ratio: 1200:1

• Luminance: 310 cd/m²

• Viewing Angle: 80° Left, 80° Right,

80° Upper, 80° Lower

• Touch Screen: Projected capacitive

Audio

- SIP v1 (RFC2543), SIP v2 (RFC3261)
- Narrowband audio codec: G.711a, G.711µ, G.729
- Broadband audio codec: G.722
- DTMF: In-band, out-of-band DTMF (RFC2833), SIP Info
- Echo Cancellation
- Voice Activation Detection
- Comfort Noise Generator
- Automatic Gain Control

Video

• Streaming formats: H.263 & H.264

Networking

Protocols support: IPv4, HTTP, HTTPS, FTP, TFTP,
 SNMP, DNS, SNTP, RTSP, SRTP, RTP, TCP, UDP,
 TLS, ICMP, DHCP, ARP

Deployment & Maintenance

- Auto-Provisioning
- Web management portal
- Web-based packet dump
- Configuration backup / restore
- Firmware upgrade
- System logs (include door access logs)

Voice Assistant

- Voice pickup distance up to 5 meters
- Voice recognition accuracy up to 95%
- Privacy protection with native voice data
- Support English

Application Scenario

- Villas
- Apartment complexes
- Home automation systems
- Modern interiors

