



CooVox-T100

CooVox-T100 is an easy-to-config and delicate diminutive IPPBX system specially designed for small and medium-sized enterprises worldwide. CooVox-T100 is well suited for small businesses with up to 100 people and meets all the needs of an office phone system. When used with the EX16S Expansion Box, T100 supports mixed networking of analog phones and VoIP phones. External lines can be selected from analog lines or VoIP lines. Equipped with the brand-new software 4.0 system, CooVox-T100 can provide users with more convenience in application and management. Plus, improve enterprise communication efficiency, and help enhance enterprise value.

ZYCOO Co., Ltd.







Venue





Mine





Factory







National Park

Feature Highlights



Endpoints Provisioning

Quick and straightforward deployment of endpoint devices using the Plug-and-Play auto-provisioning feature. Users can scan the QR code to complete the registration on the CooCall softphone.



Proxy Services

No fixed public IP, third-party DDNS services, and VPN router are required. Remote extension and remote branch office phone system integration have never been easier!



CooCall Softphone

CooCall softphone brings users a new office phone system experience while using the CooVox IPPBX v4. CooCall is like a desk phone that can take your office anywhere. Users can answer calls, dial calls, and even dial international calls through the office's IPPBX.



3rd Party Compatible

In addition to the built-in phone system functions, CooVox -T100 is also compatible with third-party SIP systems, including standard SIP endpoints, CRM systems, and collaboration tools to expand the existing IP voice communication function.



Expansion Box Provisioning

The EX16S Expansion Box can help users to deploy analog phones and fax machines on a large scale in a brief time. Both local and remote deployments are equally simple and rapid.



Operator Panel

The Operator Panel is a comprehensive software specially designed for the CooVox series of IPPBX. By using the Operator Panel, users can achieve features such as live paging, emergency paging, high-quality background music, scheduled paging, scheduled music, etc.



The control center can manage each authorized PBX in a unified manner through the remote management system, realizing remote switching off equipment, viewing real-time data, and collaborative user troubleshooting.



Billing

With a built-in billing system, no third-party billing software is required.Prepaid/postpaid billing, billing credit, flexible billing rates, and billing statistics features are all supported.

+862885337096 www.zycoo.com

Hardware Specifications

Specifications

analog interface	2 Port (Interface standard RJ11; FXO outside line or FXS inside line)		
CPU	ARM 4 Core		
RAM	1GB		
Storage (SD Card)	8G SD Card (Industrial grade)		
USB (Extended Storage Supported)	1 Port (File system format: FAT16, FAT32, EXTFAT, NTFS, EXT3, EXT4		
Ethernet Interface	WAN, LAN (10/100Mbps)		
Console Port	1 Port(Rate 115200)		
Reset Key	Support		
Power	DC 12V-1A		

Software Specifications

System Capacity	 ✓ 100 Extensions ✓ 50 Simultaneous Calls ✓ 30 Conference Attendees ✓ 400 hrs Recording (Internal Storage) ✓ 6 EX16S Deployment (Recommended) 	☑ Unlimited Pho	CLevels E mber of Queues onebook Contacts E Paging Members	 500000 CDR History 1TB USB Expansion Storage Unlimited Number of Incoming Routes Unlimited Number of Outbound Routes 	
Protocols & Codecs	 SIP(RFC3261), IAX2 DTMF(RFC4733, SIPINFO,In-Band) Transport Protocols:UDP,TCP,TLS,SRTP Network Protocols:IPv4, IPv6, VLAN, DHCP, PPPoE, DDNS, NTP, SNTP, TFTP, SSH, HTTPS, LDAP Video Codecs:VP8,H.264,H.263+,H.263,H.261 Audio Codecs:Opus, G.722, G.711(a-law,u-law), G.729, G.726, GSM, SPEEX,AMR,AMR-WB 				
Telephony Features	☑ Ring Group ☑ C ☑ Call Forward ☑ \ ☑ Call Transfer ☑ C ☑ Call Pickup ☑ C ☑ Call Parking ☑ F ☑ Call Waiting ☑ C ☑ Speed Dial ☑ C	Caller ID Call Spy /ideo Call 3-way Calling Conference Call Follow Me Call Back DISA Smart DID	 Blacklist Voicemail Wakeup Call PIN Code Do Not Disturb Switch Call Time Conditions Paging & Interco 	(WebRIC)	
Feature Highlights	 Remote Management Softphone APP Auto Provisioning (QR Code Scan) IP Phone Auto Provisioning (PNP & Quick Register Code) LDAP Phonebook Auto Configure (H81, H83) EX16S Auto Provisioning SIP Proxy (NAT Traversal) Open API Interface for Secondary Development to Connect with 3rd Systems Multilingual Interface: Simplified Chinese, Traditional Chinese, English, Spanish, Czech, Korean Multilingual System Voice: Chinese, English, Spanish, French and other 24 languages 				

+862885337096 🔪 www.zycoo.com

ZYCOO Co., Ltd.

Multi-level User Administration	 Admin user: All Privileges Operator user: Extensions, faxes, CDR, recordings, etc. Extension user: WebRTC, recordings, voicemails, call logs, etc. Billing user Operator panel user 	
Security	 Firewall based on iptables Geo-IP (Security policy based on IP address geographical locations) Intrusion auto detection and prevention IP Black/White List Extension Permit IP Data Backup and Recovery 	
Network Features	 Network (WAN): Static IP, DHCP, PPPoE VPN: PPTP, OpenVPN, Static Routing DHCP Server VLAN (WAN&LAN Interface) Virtual IP SIP Proxy (NAT Traversal) 	



No. 1602, 16th Floor, Building No. 599, Century City South Road, High-tech Zone, Chengdu, Sichuan Province, China +86 28 85337096 zycoo@zycoo.com